ConSeal™ CS-1800

Solvent Free, Waterproofing Membrane





Solvent Free Waterproofing Membrane for Most Construction Materials

Applications

ConSeal CS-1800 Waterproofing Membrane is a cold-applied single component, waterproofing compound that cures by exposure to atmospheric and substrate moisture to form a continuous, tough, reinforced elastic waterproof seal. In above grade applications, use CS-1800 to seal manhole riser systems, vertical panel structures, and a variety of concrete structures.

In below grade applications, CS-1800 is ideal as a positive-side waterproofing for sealing foundations, waterproofing box culvert, septic tanks and other underground construction. ConSeal CS-1800 is solvent free and compliant with all known environmental and OSHA requirements. It can be used in confined spaces without respiratory protection. CS-1800 forms an elastomeric rubber that is resistant to thermal shock. It will not crack in extreme cold or slump due to softening at high temperatures like conventional asphalt or coal tar based coating often will.

Green Standards

NAHB Model Green Home Building Guidelines: 5 Global Impact Points VOC Content: less than 26 grams/liter ASTM D2369 EPA Method 24 (tested at 240°F & includes water)

Advantages

Bonds to asphalt and concrete Solvent free, 100% solids, will not shrink 10 minute skin over, no dirt pick up Superior adhesion to most construction materials

Storage

Store original, unopened containers in a cool, dry area. Protect unopened containers from water, heat, and direct sunlight. Elevated temperatures will reduce shelf life.

Regulatory Compliance

Conforms to OTC Rule for Sealants & Caulks
Meets requirements for California Regulations:
CARB, BAAQMD, and SCAQMD
Conforms to California Proposition 65
Conforms to USDA Requirements for Non-Food Contact

Packaging

2 gallon pails - 60 pails per pallet

Shelf Life

Pails have a shelf life of 9 months when stored properly See Application Guide and MSDS for proper storage procedures.

Don't Just Seal It, ConSeal It!

© 2013 Concrete Sealants, Inc.



ConSeal™ CS-1800

Solvent Free, Waterproofing Membrane





Solvent Free Waterproofing Membrane for Most Construction Materials

P	h۱	/Si	ca	ΙP	ro	p	e	rti	es

Property	Typical Value	Test Method			
Solids Content	100%	ASTM D-1644			
By Weight					
Solids Content	100%	ASTM D-2697			
By Volume					
Tensile Strength	95 psi	ASTM D-2370			
Elongation	350%	ASTM D-2370			
Tack Free Time	100 minutes	ASTM C-679			
Water Vapor Transmission	0.06 perm inches	ASTM E-96			
Shore OO	60-64	ASTM D-2240			
Hardness					
Shore A	10 +/- 3	ASTM C-661			
Hardness					
Low Temperature	Pass 1/4 inch mandrel	ASTM D-816			
Flex	20°F (-29°C)				
Shrinkage	No measurable shrinkage after 14 days				
Service Temperature	-40°F to 200°F (-40°C to 94°C)				
	continuous service				

Limited Warranty

This information is presented in good faith, but we cannot anticipate all conditions under which this information and our products, or the products of other manufactures in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combinations for their own purposes. It is the **users' responsibility** to satisfy himself as to the suitability and completeness of such information for this own particular use. We sell this product without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of this product, whether used alone or in combination with other products.

Don't Just Seal It, ConSeal It!

© 2013 Concrete Sealants, Inc.

